



CITY OF REHOBOTH BEACH, DELAWARE WWTP EFFLUENT PUMPING STATION PROJECT NUMBER: 2017-003 PERMIT SUBMITTAL



GENERAL NOTES:

 LOT ADDRESS 20573 ROOSEVELT ST REHOBOTH BEACH, DE 1997

75° 05' 30" W

OWNER: CITY OF REHOBOTH BEACH 3. LATITUDE


 DISTRICT - MAP -PARCEL 334-19.00-171.01


MEDIUM RESIDENTA LOT SIZE: 19.35 ACRES

ADC MAP: MAP 27; GRID A2

8. HORIZONTAL DATUM: VERTICAL DATUM:

10. STANDARD RESPONSIBILITY NOTES, CONSULTANTS CERTIFICATION, AND





NOT TO SCALE

LCS | KSG | 06/16 ∖ ∣ PERMIT SUBMITTAL Revision Note: * indicates signatures on original issue of drawing or last revision of drawing

FOR PERMIT SUBMITTAL NOT FOR CONSTRUCTION



16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA T 1 240 206 6810 F 1 240 206 6811 **E** bowmail@ghd.com **W** www.ghd.com

Drawn	CTF		Designer	JMP	Client
Diawii			Doolgiloi	01411	Project
Drafting Check	JFM		Design Check	LCS	Title
Approved (Project D	irector)	KSG			
Date		06/2016			Contrac
	_		This Dra	wing shall not be used	Original Si

Scale NOT TO SCALE

CITY OF REHOBOTH BEACH, DELAWARE REHOBOTH BEACH WWTP EFFLUENT PUMPING STATION **COVER SHEET, LOCATION AND VICINITY MAPS**

for Construction unless Signed and Sealed For Construction

Ansi D

Drawing No: 86-18691-G001


Rev: A

PRELIMINARY

LIST OF DRAWINGS

TOTAL	DIS.	SHT	DRAWING TITLE
1	0	001	GENERAL COVER SHEET, LOCATION AND VICINITY MAPS
1	G	001	LIST OF DRAWINGS, LEGENDS, ABBREVIATIONS, SYMBOLS AND DESIGN
2	G	002	CRITERIA
			CIVIL
3	С	001	OVERALL SITE AND DEMOLITION PLAN
4	С	002	YARD PIPING PLAN
5	С	003	EROSION AND SEDIMENT CONTROL PLAN
6	С	004	EROSION AND SEDIMENT CONTROL NOTES
7	С	005	EROSION AND SEDIMENT CONTROL DETAILS
8	С	006	MISCELLANEOUS CIVIL DETAILS
			STRUCTURAL
9	S	001	PLANS, SECTIONS, AND DETAILS
			MECHANICAL
10	M	001	DESIGN CRITERIA, PUMP CURVE, AND MECHANICAL LEGEND
11	M	002	POST AERATION TANK DEMOLITION PLANS
12	M	003	EFFLUENT PUMPING STATION PLANS AND ISOMETRIC
13	M	004	EFFLUENT PUMPING STATION SECTIONS
14	M	005	MISCELLANEOUS MECHANICAL DETAILS
			HEATING/VENTILATION & AIR CONDITIONING
15	Н	001	SCHEDULES, SYMBOLS, ABBREVIATIONS AND NOTES, UV BUILDING DEMOLITION, EFFLUENT CONTROL BUILDING PLAN
			ELECTRICAL
16	Е	001	LEGENDS, ABBREVIATIONS, AND SYMBOLS
17	Е	002	ELECTRICAL PARTIAL SITE PLAN
18	Е	003	MOTOR CONTROL CENTER MCC-ECB ONE-LINE DIAGRAM
19	E	004	UV BUILDING, POST AERATION TANK, AND PARSHALL FLUME DEMOLITION PLANS
20	Ε	005	EFFLUENT PUMPING STATION POWER AND CONTROL PLAN
21	Ε	006	EFFLUENT CONTROL BUILDING POWER AND CONTROL PLAN
22	E	007	EFFLUENT PUMPING STATION AND EFFLUENT CONTROL BUILDING CONDUIT RISER DIAGRAMS
23	Ε	800	EQUIPMENT SCHEDULES
24	Ε	009	ELECTRICAL ELEMENTARIES
25	Ε	010	ELECTRICAL DETAILS 1
26	Ε	011	ELECTRICAL DETAILS 2
27	Ε	012	ELECTRICAL DETAILS 3

MISCELLANEOUS SYMBOLS



GENERAL LEGEND


NEW GRAPHICS; EQUIPMENT, STRUCTURES, ETC., ARE SHOWN AS BOLD LINEWORK AND IN THIS TEXT FORMAT

EXISTING GRAPHICS; EQUIPMENT, CONDITIONS STRUCTURES, ETC. ARE SHOWN AS LIGHT LINEWORK AND IN THIS TEXT FORMAT.


EXISTING PIPE CALLOUT (FOR PLANS)




NEW PIPE CALLOUT (FOR PLANS)



NEW/EXIST PIPE CALLOUT (FOR SECTIONS)




TYPICAL SECTION MARKS (FOR PLANS)



DEPICTION BOUNDARY

TYPICAL SECTION SUB-TITLE (FOR SECTIONS)




SECTION LETTER -

DRAWING NUMBER

(REPRESENTS DRAWING

WHERE DETAIL IS DRAWN)

NORTH ARROW



COMBINATION SEWAGE AIR/ VACUUM VALVE ARV

LIST OF ABBREVIATIONS

CENTER LINE

- CONC CONCRETE CP CONSTRUCTION POINTS CV CHECK VALVE DIP DUCTILE IRON PIPE
- ELEVATION FM FORCE MAIN
- FRP FIBERGLASS REINFORCED PLASTIC HDPE HIGH DENSITY POLYETHYLENE
- LOD LIMIT OF DISTURBANCE MJ MECHANICAL JOINT
- PHC POINT OF HORIZONTAL CONTACT PHT POINT OF HORIZONTAL TANGENCY
- PV PLUG VALVE
- PVC POLYVINYL CHLORIDE PVC POINT OF VERTICAL CONTACT
- PVT POINT OF VERTICAL TANGENCY MH MANHOLE
- RP ROAD CONSTRUCTION POINT STANDARD
- STD STA STATION

Plot Date: 17 June 2016 - 11:03 AM

GENERAL NOTES

- EXISTING CONDITIONS SHOWN ON THESE CONTRACT DRAWINGS WERE OBTAINED FROM AVAILABLE CONTRACT AND RECORD DRAWINGS AND A SURVEY PERFORMED IN OCTOBER 2015 BY AXIOM ENGINEERING, LLC AND THEREFORE THEIR LOCATION MUST BE CONSIDERED APPROXIMATE ONLY. IT IS THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL EXISTING FIELD CONDITIONS.
- CONTRACTOR TO REPAIR AND RESTORE ANY ADJACENT ROADWAYS, DRIVEWAYS, CURB, SIDEWALKS, UTILITIES, STORM DRAINS, CULVERTS, SWALES, CLEANOUTS, STRUCTURES, EQUIPMENT, AND/OR SUBGRADE THAT IS EXPOSED, DISTURBED, OR OTHERWISE DAMAGED BY THE CONTRACTOR'S ACTIVITIES.
- CONTRACTOR SHALL MINIMIZE DISTURBANCE TO LIMIT REMOVAL OF TREES AND OTHER VEGETATION. CONTRACTOR IS RESPONSIBLE FOR ALL COSTS ASSOCIATED WITH CUTTING DOWN, REMOVAL, AND DISPOSAL OF ANY TREES AND VEGETATION, ALONG WITH THE COST ASSOCIATED WITH REPLACING ALL VEGETATION WITH SIMILAR SPECIES.
- 4. EXISTING PAVEMENT SHALL BE PROTECTED FROM DAMAGE WHERE POSSIBLE. ANY DEMOLISHED OR DAMAGED PAVEMENT TO BE REPAIRED.
- 5. CONTRACTOR TO FIELD VERIFY LOCATIONS OF EXISTING PIPING AND STRUCTURES.
- 6. CONTRACTOR SHALL CONFORM WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL CODES DURING TRENCHING ACTIVITIES.
- 7. ALL EXISTING PIPING, EQUIPMENT, AND STRUCTURES MUST BE FULLY SUPPORTED DURING CONSTRUCTION AGAINST VERTICAL, HORIZONTAL, AND OVERTURNING FORCES AND MOVEMENT.
- 8. ALL JOINTS ON PRESSURE PIPE AND FITTINGS SHALL BE FULLY RESTRAINED.
- 9. POWER LINE POLES TO BE PROTECTED AS REQUIRED DURING CONSTRUCTION OF THE FORCE MAINS.
- 10. CONTRACTOR SHALL SUPPLY ALL BENDS REQUIRED TO MAINTAIN SMOOTH FLOW LINES, CHANGES IN ELEVATION AND TO MEET ALL TRANSITIONS.
- 11. CONTRACTOR SHALL REPLACE ALL PAVEMENT AND ROADWAYS THAT IS 1) SHOWN AS REPLACED ON THE CONTRACT DRAWINGS, 2) IMPACTED BY NEW CONSTRUCTION, AND 3) IMPACTED BY CONTRACTOR'S OPERATIONS.

___X___X___

_ — — — —21— — — — —

———— OHE ————

SCE OF

POS #

(XXX)

OVERHEAD ELECTRICAL SERVICE LINES ELECTRICAL UTILITY

PROPERTY LINE

DRAINAGE AREA

SOIL DIVIDE LINE

SILT FENCE

FORCE MAIN

STORM DRAIN

WETLAND

─ 25' WETLAND BUFFER

LIMIT OF SURVEY

STABILIZED CONSTRUCTION ENTRANCE

TIME OF CONCENTRATION

POINT OF STUDY

DRAINAGE AREA

SOIL TYPE

SUB-DRAINAGE AREA

LIMIT OF DISTURBANCE

100 YEAR BASE FLOOD ELEVATION

CIVIL LEGEND

NEW STRUCTURE EXISTING PAVEMENT

EXISTING STRUCTURE

NEW PAVEMENT

EXISTING GRAVEL PAVEMENT

NEW CONCRETE PAVEMENT/ SIDEWALK

>25% SLOPES

15-25% SLOPES RIPRAP

UTILITY POLE TREE

CONSTRUCTION STAKEOUT POINT

SURVEY CONTROL POINT/ MONUMENT (BENCHMARK) CLEANOUT

TREE

LIST OF PIPING DESIGNATIONS

ABD ABANDONED CLE CHLORINATED EFFLUENT FLE FILTERED EFFLUENT PD PLANT DRAIN

PLE PLANT EFFLUENT UW UTILITY WATER VT VENT

PRELIMINARY

LCS | KSG | 06/16 A │PERMIT SUBMITTAL

FOR PERMIT SUBMITTAL NOT FOR CONSTRUCTION



16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA T 1 240 206 6810 F 1 240 206 6811 **E** bowmail@ghd.com **W** www.ghd.com

Drawn	CTF		Designer	JMP	Clien Proje
Drafting Check	JFM		Design Check	LCS	Title
Approved (Project D	irector)	KSG	•		
Date		06/2016			Contr

and Sealed For Construction


Scale NOT TO SCALE


ent CITY OF REHOBOTH BEACH, DELAWARE Piect REHOBOTH BEACH WWTP EFFLUENT PUMPING STATION LIST OF DRAWINGS, LEGENDS, ABBREVIATIONS, **SYMBOLS AND DESIGN CRITERIA**


This Drawing shall not be used Original Size for Construction unless Signed and Sealed For Construction

Ansi D

Drawing No: 86-18691-G002







STANDARD SEDIMENT AND EROSION CONTROL NOTES

- ALL EROSION AND SEDIMENT PRACTICES SHALL COMPLY WITH THE DELAWARE EROSION AND SEDIMENT CONTROL HANDBOOK 1989 OR LATEST EDITION.
- REVIEW AND APPROVAL OF THE SEDIMENT AND STORMWATER MANAGEMENT PLAN SHALL NOT RELIEVE THE CONTRACTOR FROM HIS OR HER RESPONSIBILITIES FOR COMPLIANCE WITH THE REQUIREMENTS OF THE SEDIMENT AND STORMWATER REGULATIONS, NOR SHALL IT RELIEVE THE CONTRACTOR FROM ERRORS OR
- IF THE APPROVED PLAN NEEDS TO BE MODIFIED, ADDITIONAL SEDIMENT AND STORMWATER CONTROL MEASURES MAY BE REQUIRED AS DEEMED NECESSARY BY THE SUSSEX CONSERVATION DISTRICT. THIS MAY RESULT IN ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES.
- FOLLOWING SOIL DISTURBANCE OR REDISTURBANCE, PERMANENT OR TEMPORARY STABILIZATION SHALL BE COMPLETED WITHIN 14 CALENDAR DAYS AS TO THE
- SURFACE OF ALL PERIMETER SEDIMENT CONTROLS, TOPSOIL STOCKPILES, AND ALL OTHER DISTURBED OR GRADED AREAS ON THE PROPOSED SITE. THE CONTRACTOR SHALL MAINTAIN AND REPAIR ALL EROSION AND SEDIMENT CONTROL PRACTICES FOR THE DURATION OF THE PROJECT.
- THE SUSSEX SOIL CONSERVATION DISTRICT RESERVES THE RIGHT TO ENTER PRIVATE PROPERTY FOR THE PURPOSES OF PERIODIC SITE INSPECTION.
- APPROVED PLANS REMAIN VALID FOR THREE YEARS FROM DATE OF APPROVAL. IF DUST BECOMES A PROBLEM DURING CONSTRUCTION, DUST CONTROL SHALL BE STABILIZED ACCORDING TO "STANDARD AND SPECIFICATIONS" FOR DUST
- CONTROL IN THE "DELAWARE EROSION AND SEDIMENT CONTROL HANDBOOK" 1989 OR LATEST EDITION. ALL SEDIMENT CONTROL DEVICES SHALL BE INSPECTED AND LEFT IN FUNCTIONAL CONDITION AT THE END OF EACH WORKING DAY.
- ANY DEVIATION FROM THE "SEQUENCE OF OPERATIONS" AS SHOWN ON THESE DRAWINGS SHALL BE APPROVED BY THE SEDIMENT CONTROL INSPECTOR.
- IF MINOR FIELD ADJUSTMENTS ARE NEEDED, THE CONTRACTOR MUST GET APPROVAL FROM THE SEDIMENT CONTROL INSPECTOR.
- INSTALLED SEDIMENT CONTROL DEVICES SHALL FULLY PROTECT TRENCH EXCAVATION, STOCKPILES AND OTHER AREAS DISTURBED DURING CONSTRUCTION. WHEN SLOPES ARE 3:1 OR GREATER, EROSION CONTROL MATTING IS REQUIRED. 13.
- NO SPOILS, STOCKPILED OR EXCAVATED MATERIAL MAY BE DISCHARGED INTO WETLANDS REGULATED BY THE ARMY CORP OF ENGINEERS OR THE STATE OF
- DELAWARE. NO SPOILS SHALL ENTER STREAMS, CHANNELS OR WATERWAYS. MEASURES SUCH AS SILT FENCE, OR BUFFER STRIPS SHALL BE USED TO PROTECT STREAMS,
- CHANNELS PONDS OR WATERWAYS. THE DISTRICT INSPECTOR MAY AT HIS DISCRETION SELECT THE INSTALLATION LOCATION. THE SUSSEX COUNTY CONSERVATION DISTRICT SHALL BE NOTIFIED PRIOR TO ANY WELLPONT OPERATIONS FOR DEWATERING. ANY WATER ENCOUNTERED DURING
- CONSTRUCTION SHALL BE FILTERED THROUGH AN APPROVED SEDIMENT REMOVING DEVICE AS INDICATED ON THE PLANS. ALL WATER DISCHARGED FROM SEDIMENT DEVICES MUST BE DISCHARGED TO AN APPROVED SITE. THE DISCHARGE OF WATER FROM SEDIMENT TANKS DIRECTLY TO TIDAL WATERS OR WETLANDS IS PROHIBITED.
- 17. SEDIMENT CONTROL DEVICES CONSTRUCTED WITHIN DITCH AREAS SHALL BE REMOVED ONLY WHEN PERFORMING TRENCH EXCAVATION, BACKFILL OR GRADING OF THE DITCH. REMOVED DEVICES SHALL BE RE-INSTALLED IMMEDIATELY FOLLOWING DISTURBANCE.
- SALVAGE EXISTING TOPSOIL FROM THE CONSTRUCTION AREA.
- STOCKPILES OF MATERIAL SHALL BE ON A RELATIVELY FLAT SURFACE. STOCKPILES MUST BE SURROUNDED WITH SILT FENCE OR STABILIZED EARTH BERM.
- NO MATERIAL OUTSIDE OF CONTRACT AREA IS ALLOWED TO BE STOCKPILED IN THIS SITE. A SEPARATE APPROVED SEDIMENT CONTROL PLAN IS REQUIRED. MATERIAL REMOVED AS A RESULT OF EXCAVATION FROM ROAD SURFACE, GRAVEL, SANDROADS AND STOCKPILED FOR RE-USE SHALL BE PROTECTED WITH
- APPROVED SEDIMENT CONTROL PRACTICE. THE METHOD SHALL BE REVIEWED WITH THE SUSSEX CONSERVATION DISTRICT INSPECTOR PRIOR TO CONSTRUCTION. CONTRACTOR SHALL KEEP ALL ROADS OR STREETS ADJACENT TO THE CONSTRUCTION SITE CLEAN OF DEBRIS OR SEDIMENT. STREET CLEANING AND REMOVAL OF
- ANY SEDIMENT SHALL BE ACCOMPLISHED AT THE END OF EACH WORKING DAY OR PRIOR TO RAIN OR WHEN FIELD CONDITIONS DICTATE. APPROVAL OF A SEDIMENT AND STORMWATER PLAN DOES NOT GRANT OR IMPLY RIGHT TO DISCHARGE STORMWATER RUNOFF. THE OWNER/DEVELOPER IS
- RESPONSIBLE FOR ACQUIRING ANY AND ALL AGREEMENTS, EASEMENTS, ETC., NECESSARY TO COMPLY WITH STATE DRAINAGE AND OTHER APPLICABLE LAWS.
- THE COUNTY SHALL BE RESPONSIBLE FOR THE MAINTENANCE OF ALL FILTER STRIPS.

SEQUENCE OF OPERATIONS

- THE SUSSEX CONSERVATION DISTRICT MUST BE NOTIFIED IN WRITING FIVE (5) DAYS PRIOR TO COMMENCING WITH CONSTRUCTION. FAILURE TO DO SO CONSTITUTES A VIOLATION OF THE APPROVED SEDIMENT AND STORMWATER MANAGEMENT PLAN.
- CONDUCT A PRE-CONSTRUCTION MEETING.
- CLEAR AND GRUB FOR ALL AREAS NECESSARY FOR THE INSTALLATION OF PERIMETER CONTROLS.
- 4. INSTALL PERIMETER CONTROLS AND ALL OTHER SEDIMENT AND EROSION CONTROL MEASURES AS SHOWN OR CALLED FOR ON THE DRAWINGS INCLUDING STABILIZED CONSTRUCTION ENTRANCES AND SILT FENCE.
- EXCAVATE TRENCH, INSTALL PIPELINES AND BACKFILL. ALL TRENCHES SHALL BE BACKFILLED DURING THE SAME DAYLIGHT PERIOD THAT THEY HAVE BEEN EXCAVATED. ANY GROUNDWATER PUMPED DURING CONSTRUCTION SHALL BE DISCHARGED TO THE LEWES-REHOBOTH CANAL. CANAL SHALL BE PROTECTED FROM EROSION DURING THIS OPERATION. ANY SEDIMENT LADDEN WATER REMOVED FROM EXCAVATIONS SHALL BE FILTERED THROUGH A DEWATERING BASIN ACCEPTABLE TO THE SUSSEX CONSERVATION DISTRICT.
- PERFORM TREATMENT FACILITIES MODIFICATIONS
- AS WORK PROGRESSES, RETOPSOIL COMPLETE PORTIONS USING SALVAGED TOPSOIL, FINE GRADE AND APPLY PERMANENT SEEDING AS NOTED. IF OUT OF SEASON APPLY TEMPORARY SEEDING UNTIL PERMANENT SEEDING CAN BE PERFORMED.
- RESTORE ALL DISTURBED AREAS TO THE ORIGINAL GRADE AND VEGETATE AS REQUIRED.
- REMOVE SEDIMENT AND EROSION CONTROL DEVICES AFTER AREA HAS BEEN COMPLETELY STABILIZED (WITH PRIOR APPROVAL OF THE SEDIMENT AND

EROSION CONTROL INSPECTOR.) START CONSTRUCTION: TBD END CONSTRUCTION: TBD

PERMANENT SEEDINT NOTES

APPLY TO GRADED OR CLEARED AREAS NOT SUBJECT TO IMMEDIATE FURTHER DISTURBANCE WHERE PERMANENT LONG LIVED VEGETATIVE COVER IS NEEDED.

LOOSEN UPPER THREE INCHES BY RAKING, DISCING OR OTHER ACCEPTABLE MEANS BEFORE SEEDING.

SOIL AMENDMENTS

IN LIEU OF SOIL TEST RECOMMENDATIONS. USE THE FOLLOWING. APPLY 2 TONS PER ACRE DOLOMITIC LIMESTONE (92 LBS/1000 SQ.FT.) AND 600 LBS. PER ACRE 10-10-10 FERTILIZER (14 LBS/1000 SQ.FT.) BEFORE SEEDING, HARROW OR DISC INTO UPPER THREE INCHES OF SOIL.

FOR THE PERIODS MARCH 1 THRU APRIL 30, AND AUGUST 1 THRU OCTOBER 15, SEED WITH 150 LBS. PER ACRE (1.4 LBS.1000 SQ.FT.) OF KENTUCKY 31 TALL FESCUE. FOR THE PERIOD MAY 1 THRU JULY 31, SEED WITH 150 LBS. KENTUCKY 31 TALL FESCUE PER ACRE AND 6 LBS. PER ACRE (0.05 LBS./1000 SQ.FT.) OF WEEPING LOVEGRASS. DURING THE PERIOD OF OCTOBER 16 THRU FEBRUARY 28 PROTECT SITE BY: OPTION (1) 2 TONS PER ACRE OF WELL ANCHORED STRAW MULCH, AND SEED AS SOON AS POSSIBLE IN THE SPRING. OPTION (2) USE SOD. OPTION (3) SEED WITH 60 LBS. PER ACRE KENTUCKY 31 TALL FESCUE AND MULCH WITH 2 TONS PER ACRE WELL ANCHORED STRAW.

APPLY 1 1/2 TO 2 TONS PER ACRE (70 TO 90 LBS./1000 SQ.FT.) OF-UNROTTED SMALL GRAIN STRAW IMMEDIATELY AFTER SEEDING. ANCHOR MULCH IMMEDIATELY AFTER APPLICATION USING MULCH ANCHORING TOOL OR 218 GALLONS PER ACRE (5 GAL./1000 SQ.FT.) OF EMULSIFIED ASPHALT ON FLAT AREAS. ON SLOPES 8 FT. OR HIGHER USE 348 GALLONS PER ACRE (8 GAL./1000 SQ.FT.) FOR ANCHORING.

INSPECT ALL SEEDED AREAS AND MAKE REPAIRS IF NEEDED. RESEED IF NECESSARY.

TEMPORARY SEEDING NOTES

APPLY TO GRADED OR CLEARED AREAS LIKELY TO BE REDISTURBED WHERE A SHORT-TERM VEGETATIVE

LOOSEN UPPER THREE INCHES OF SOIL BY RAKING, DISCING OR OTHER ACCEPTABLE MEANS BEFORE

SOIL AMENDMENTS APPLY 600 LBS. PER ACRE 10-10-10 FERTILIZER (14 LBS/1000 SQ.FT.)

FOR PERIOD MARCH 1 THRU APRIL 30 AND FROM AUGUST 15 THRU NOVEMBER 15 SEED WITH 2 1/2 BUSHELS PER ACRE OF ANNUAL RYE (3.2 LBS/1000 SQ.FT.). FOR PERIOD FROM MAY 1 THRU AUGUST 14, SEED WITH 3 LBS. PER ACRE OF WEEPING LOVEGRASS(0.07 LBS/1000 SQ.FT.). FOR THE PERIOD NOVEMBER 16 THRU FEBRUARY 28, PROTECT SITE BY APPLYING 2 TONS PER ACRE OF WELL ANCHORED STRAW MULCH AND SEED AS SOON AS POSSIBLE IN THE SPRING OR USE SOD.

APPLY 1 1/2 TO 2 TONS PER ACRE (70 TO 90 LBS./1000 SQ.FT.) OF UNROTTED SMALL GRAIN STRAW IMMEDIATELY AFTER SEEDING, ANCHOR MULCH IMMEDIATELY AFTER APPLICATION USING MULCH ANCHORING TOOL OR 218 GALLONS PER ACRE (5 GAL./1000 SQ.FT.) OF EMULSIFIED ASPHALT ON FLAT AREAS, ON SLOPES 8 FT. OR HIGHER, USE 348 GAL. PER ACRE (8 GAL./1000 SQ.FT.) FOR ANCHORING.

	SITE ANAL	YSIS				
A.	TOTAL LIMITS OF DISTURBED AREA	±0.24 Ac				
B.	TOTAL LENGH OF SILT FENCE	±285 LF				
C.	TOTAL CUT	N/A				
D.	TOTAL FILL	N/A				
E.	OFF-SITE WASTE/BORROW AREA LOCATION	N/A				
¹ STR	UCTURE EXCAVATION AND BACKFILL QUAI	NTITIES NOT INCLUDED				

SOILS T	ABLE
SOIL TYPE	UfB, UDORTHENTS
HYDRIC RATING	0
EMBANKMENTS, DIKES AND LEVEES	SOMEWHAT LIMITED. REFUSE/SUBSTRATUM 85%
EXCAVATED PONDS (AQUIFER-FED)	SOMEWHAT LIMITED. REFUSE/SUBSTRATUM 85%, BORROW AREA 3&
POND RESERVOIR AREA	SOMEWHAT LIMITED. REFUSE/SUBSTRATUM 85%, BORROW AREA 3&
K FACTOR - WHOLE SOIL	0.32
DRAINAGE CLASS	WELL DRAINED
HYDROLOGIC SOIL GROUP	С
DEPTH TO WATER TABLE	114 CM
FLOODING FREQUENCY CLASS	NONE
PONDING FREQUENCY CLASS	NONE

OWNER / DEVELOPER CERTIFICATION

IWE CERTIFY THAT THE INFORMATION ON THIS FORM AND THE ATTACHED PLANS IS TRUE AND ACCURATE TO THE BEST OF MY/OUR KNOWLEDGE.

IWE UNDERSTAND THAT DNREC MAY REQUEST INFORMATION IN ADDITION TO THAT SET FORTH HEREIN AS MAY BEDEEMED APPROPRIATE IN CONSIDERING THIS APPLICATION.

I/WE WILL ABIDE BY THE CONDITION OF THIS APPROVAL AS ISSUED

I/WE CERTIFY THAT ALL LAND CLEARING, CONSTRUCTION AND DEVELOPMENT SHALL BE DONE PURSUANT TO THE APPROVED ATTACHED PLANS AND THAT RESPONSIBLE PERSONNEL (I.E. BLUE CARD HOLDER) INVOLVED IN THE LAND DISTURBANCE WILL HAVE A CERTIFICATION OF TRAINING PRIOR TO INITIATION OF THE PROJECT, AT A DNREC SPONSORED OR APPROVED TRAINING COURSE FOR THE CONTROL OF EROSION AND SEDIMENT DURING CONSTRUCTION. IN ADDITION, I/WE GRANT THE DNREC SEDIMENT AND STORMWATER PROGRAM AND/OR RELEVANT DELEGATED AGENCY THE RIGHT TO CONDUCT ON-SITE

REVIEWS, AND I/WE UNDERSTAND MY/OUR RESPONSIBILITIES UNDER THE NPDES CONSTRUCTION GENERAL PERMIT, ASSOCIATED WITH THIS SITE.

OWNER / DEVELOPER SIGNATURE	DATE	

DESIGNER CERTIFICATION

PRINTED NAME AND TITLE

DESIGNER NAME AND TITLE

I HEREBY CERTIFY THAT THIS PLAN HAS BEEN PREPARED UNDER MY SUPERVISION AND TO THE BEST OF MY KNOWLEDGE COMPLIES WITH THE APPLICABLE STATE AND LOCAL REGULATIONS AND ORDINANCES.

DESIGNER SIGNATURE	DATE
PESIGNER SIGNATORE	DATE

PRELIMINARY

CTF | LCS | KSG | 06/16 A | PERMIT SUBMITTAL No Revision Note: * indicates signatures on original issue of drawing or last revision of drawing

NOT FOR CONSTRUCTION

FOR PERMIT SUBMITTAL



16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA T 1 240 206 6810 F 1 240 206 6811 **E** bowmail@ghd.com **W** www.ghd.com

Designer JMP CTF Drawn Drafting Check LCS Approved (Project Director) KSG This Drawing shall not be used Original Size Scale NOT TO SCALE

CITY OF REHOBOTH BEACH, DELAWARE REHOBOTH BEACH WWTP EFFLUENT PUMPING STATION **EROSION AND SEDIMENT CONTROL NOTES**


for Construction unless Signed and Sealed For Construction


Ansi D


Drawing No: 86-18691-C004

Rev: A

Plotted by: Cody Ford Cad File No: G:\86\18691\CADD\Drawings\Civil\86-18691-C004.dwg Plot Date: 17 June 2016 - 11:04 AM







PRELIMINARY

Rev: A

A PERMIT SUBMITTAL

CTF LCS KSG 06/16

No Revision Note: * indicates signatures on original issue of drawing or last revision of drawing Drawn Manager Director Date

FOR PERMIT SUBMITTAL NOT FOR CONSTRUCTION



Source:

Adapted from

Colorado Urban Storm Drainage

Criteria Manual, Vol 3

Symbol:

Drawn CTF

Designer JMP

Pro

Drafting Check

Approved (Project Director)

Date

Design LCS

Titl

Cli

Pro

Check

Check

Co

Co

Co

Client Project CITY OF REHOBOTH BEACH, DELAWARE REHOBOTH BEACH WWTP EFFLUENT PUMPING STATION

Title EROSION AND SEDIMENT CONTROL DETAILS

16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA
T 1 240 206 6810 F 1 240 206 6811
E bowmail@ghd.com W www.ghd.com

Date

06/2016

Contract No.
This Drawing shall not be used for Construction unless Signed
Ansi D

Detail No.

DE-ESC-3.7.3

Sheet 2 of 2

03/13


for Construction unless Signed and Sealed For Construction

Ansi D

Drawing No: 86-18691-C005

Plot Date: 17 June 2016 - 11:05 AM Plotted by: Cody Ford


Cad File No: G:\86\18691\CADD\Drawings\Civil\86-18691-C005.dwg



NOTES:

- FOUNDATION MATERIAL ONLY REQUIRED WHEN UNSUITABLE SUBGRADE MATERIALS ENCOUNTERED.
- 2. SEE SPECIFICATION 0223 (BACKFILLING) FOR MATERIALS REQUIRED.
- 3. REINFORCING GEOTEXTILE FABRIC SHALL BE USED FOR STABILIZATION. FABRIC SHALL WRAP TRENCH BOTTOM TO A MINIMUM HEIGHT OF 6" ABOVE INITIAL BACKFILL.







PRELIMINARY

A PERMIT SUBMITTAL

CTF LCS KSG 06/16

No Revision Note: * indicates signatures on original issue of drawing or last revision of drawing Drawn Manager Director Date

FOR PERMIT SUBMITTAL NOT FOR CONSTRUCTION



16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA T 1 240 206 6810 F 1 240 206 6811 E bowmail@ghd.com W www.ghd.com

Drawn CTF		Designer	JMP	Client Project
Drafting JFM Check		Design Check	LCS	Title
Approved (Project Director)	KSG			
Date	06/2016			Contract

Scale NOT TO SCALE

Client CITY OF REHOBOTH BEACH, DELAWARE
Project REHOBOTH BEACH WWTP EFFLUENT PUMPING STATION
Title MISCELLANEOUS CIVIL DETAILS

MISCELLANEOUS CIVIL DETA


This Drawing shall not be used for Construction unless Signed and Sealed For Construction

Original Size

Ansi D

Drawing No: 86-18691-C006

1-C006 Rev: A





DESIGN CRITERIA

MINIMUM DETENTION TIME, TOTAL

PIPE FITTINGS AND VALVE SYMBOLS

DESIGN FLOWS	
WINTER MINIMUM FLOW	0.6 MGD
AVERAGE DAY FLOW	3.5 MGD
SUMMER PEAK FLOW	7.2 MGD
EFFLUENT PUMPS	
LOCATION	EFFLUENT PUMPING STATION
NO. OF UNITS	2 DUTY + 1 SPARE
TYPE	VERTICAL TURBINE
MINIMUM CYCLE TIME	9.14 MIN
PUMP OPERATING FLOWS	
ONE PUMP MAX SPEED	2,500 GPM @ 63 FT
TWO PUMP MAX SPEED	5,000 GPM @ 60 FT
WET WELL	
NUMBER OF WET WELLS	2
WET WELL SURFACE AREA, EACH	225 SF
OPERATING DEPTH	2.4 FT
OPERATING VOLUME, EACH	4,040 GAL





1.62 MIN

SINGLE LINE PIPING SYMBOLS PIPE SUPPORT SYMBOLS **SECTION** ELBOW UP DUAL BRACKET VERTICAL PIPE SUPPORT **ELBOW DOWN** 90° ELBOW IN PLANE ANGLE BRACKET PIPE SUPPORT 45° ELBOW IN PLANE TYPE 1 PIPE SUPPORT TEE IN PLANE TYPE 38 PIPE SUPPORT FIXED PIPE SUPPORT $\longleftarrow \bigcirc \longrightarrow$ CONCENTRIC REDUCER $\longleftarrow \Box$ ECCENTRIC REDUCER SLIDING PIPE SUPPORT CONE TYPE SPRAY NOZZLE FAN TYPE SPRAY NOZZLE

PUMP CURVE

PRELIMINARY

CTF LCS KSG 06/16 A | PERMIT SUBMITTAL Drawn Job Project Director Date No Revision Note: * indicates signatures on original issue of drawing or last revision of drawing

FOR PERMIT SUBMITTAL NOT FOR CONSTRUCTION



16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA **T** 1 240 206 6810 **F** 1 240 206 6811 **E** bowmail@ghd.com **W** www.ghd.com Scale NOT TO SCALE

Drawn	CTF		Designer	JMP	Client
Diawii	<u> </u>		Designer	Olvii	Project
Drafting Check	JFM		Design Check	LCS	Title
Approved (Project Dir	rector)	KSG			
Date		06/2016			Contra

This Drawing shall not be used Original Size


CITY OF REHOBOTH BEACH, DELAWARE REHOBOTH BEACH WWTP EFFLUENT PUMPING STATION DESIGN CRITERIA, PUMP CURVE


AND MECHANICAL LEGEND

for Construction unless Signed and Sealed For Construction

Ansi D


Drawing No: 86-18691-M001 Rev: A





POST AERATION TANK - UPPER LEVEL DEMOLITION PLAN

SCALE: 3/8" = 1'-0"



LEGEND: TO BE DEMOLISHED

DEMOLITION NOTES:


- 1. EXISTING HANDRAILS ARE TO BE DEMOLISHED. STRUCTURES AND EQUIPMENT SPECIFICALLY REFERENCED FOR DEMOLITION SHOWN ON THIS SHEET ARE FOR CONTRACTOR'S REFERENCE ONLY.
- 2. REFER TO GENERAL SHEETS FOR ADDITIONAL DEMOLITION
- 3. PORTABLE ASPIRATORS TO BE SALVAGED BY OWNER.


PRELIMINARY


CITY OF REHOBOTH BEACH, DELAWARE FOR PERMIT SUBMITTAL Designer JMP Drawn JDH NOT FOR CONSTRUCTION Project REHOBOTH BEACH WWTP EFFLUENT PUMPING STATION SCALE 3/8"=1'-0" AT ORIGINAL SIZE Drafting JFM Check **T5: POST AERATION TANK DEMOLITION PLANS** Approved (Project Director) KSG GHD Inc. Date 4/16 16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA T 1 301 805 5629 F 1 301 805 4665 Contract No LCS KSG 06/16 A PERMIT SUBMITTAL This Drawing shall not be used for Construction unless Signed and Sealed For Construction

Original Size Ansi D

Drawing No: 86-18691-M002 **E** bowmail@ghd.com **W** www.ghd.com Drawn Job Project Director Date Scale 3/8" = 1'-0" Rev: A No Revision Note: * indicates signatures on original issue of drawing or last revision of drawing







Plot Date: 17 June 2016 - 11:05 AM Plotted by: Cody Ford Cad File No: G:\86\18691\CADD\Drawings\Mech\86-18691-M005.dwg


SPLIT S	SYSTEM DUCTLES	S HEAT PUMP UNIT SCHEDUL	E											
								INDOC	R UNIT	OUTD	OOR UNIT	CONTROLS	DESIN BASIS	
			AIRFLOW	NOMINAL	TOTAL COOLING	TOTAL HEATING		POWER REG	QUIREMENTS	POWER R	EQUIREMENTS	CONTROLLED		NOTES
UNITID	ROOM SERVED	TYPE	LOW - HIGH (CFM)	TONS COOLING	CAPACITY (MBH)	CAPACITY (MBH)	SEER (Btu/hr/W)	MCA	VOLTS/ PHASE	MCA	VOLTS/ PHASE	BY	MANUFACTURER, MODEL	
HP-1	ELECTRICAL ROOM	CEILING SUSPENDED, DUCTLESS	530 - 670	2	24.0	26.0	16.8	1	208/1	18	208/1	HP-1 TSTAT	MITSUBISHI, PCA-A24KA & PUZ-A24NHA4; OR EQUAL	1


GENERAL NOTES


- 1. COORDINATE ALL HVAC WORK WITH OTHER DISCIPLINES.
- 2. ALL ELECTRICAL EQUIPMENT AND WIRING SHALL BE IN FULL ACCORDANCE WITH DIVISION 16, ELECTRICAL, AND DIVISION 17, INSTRUMENTATION SPECIFICATIONS.
- 3. CONTRACTOR SHALL BE RESPONSIBLE FOR REPAIR RESULTING FROM DEMOLISHED EQUIPMENT, CONCRETE EQUIPMENT PADS, SUPPORTS AND MATERIALS. REPAIR AND FINISH TO MATCH EXISTING CONSTRUCTION.
- 4. CONTRACTOR SHALL BE RESPONSIBLE FOR SEALING OFF ALL INTERIOR AND EXTERIOR OPENINGS RESULTING FROM DEMOLITION WORK.

SCHEDULE NOTES

1. PROVIDE WITH CONDENSATE PUMP AND LOW AMBIENT AIR KIT.









CONDENSATE DRAIN CONNECTION DETAIL

NOT TO SCALE




PRELIMINARY








Plot Date: 17 June 2016 - 11:06 AM















DUCT BANK NOTES:

SPARE DUCTS (TYP): PROVIDE PULL STRING FOR ALL DUCTS NOTED AS SPARE.

DRAWING NOTES:

- $\langle 1 \rangle$ EXISTING SITE CONDITIONS: CONTRACTOR SHALL FIELD VERIFY AND COORDINATE ALL EXISTING PIPING ELEVATIONS, LOCATIONS, SIZES AND TYPE OF MATERIAL WITH NEW ELECTRICAL WORK PRIOR TO CONSTRUCTION. CONTRACTOR SHALL FIELD VERIFY AND COORDINATE ALL EXISTING EQUIPMENT DIMENSIONS AND ELEVATIONS PRIOR TO ORDERING NEW EQUIPMENT AND SUPPORTS. REFER TO SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.
- \langle 2 \rangle DUCT BANKS: COORDINATE DEPTH AND ROUTING OF DUCT BANKS WITH EXISTING SITE CONDITIONS AND BELOW GRADE UTILITIES. ADJUST DEPTH TO ACCOMMODATE GRADING AND SWALE/DITCH ELEVATIONS. COORDINATE FINAL DUCT BANK ROUTING AT BUILDING AND VAULT ENTRANCES TO AVOID INTERFERENCE WITH EXISTING UTILITIES. DUCT BANK SHALL BE ROUTED TO PULL BOXES OR EQUIPMENT AS SHOWN ON THE CONDUIT RISER DIAGRAMS. WHERE NO RISER DIAGRAMS ARE SHOWN, DUCTS SHALL BE EXTENDED TO THE FUNCTIONALLY ASSOCIATED EQUIPMENT. **PRELIMINARY**





Cad File No: G:\86\18691\CADD\Drawings\Elec\86-18691-E002.dwg

Plot Date: 17 June 2016 - 11:06 AM

Plotted by: Cody Ford

GHD Inc.

FOR PERMIT SUBMITTAL

NOT FOR CONSTRUCTION

Drafting Check Design Check JFM Approved (Project Director) KSG 16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA T 1 240 206 6810 F 1 240 206 6811 This Drawing shall not be used Original Size E bowmail@ghd.com W www.ghd.com Scale 1" = 20'-0"

Designer CMM JDH Drawn Contract No.


REHOBOTH BEACH WWTP EFFLUENT PUMPING STATION **ELECTRICAL PARTIAL SITE PLAN**

for Construction unless Signed and Sealed For Construction

Ansi D

Drawing No: 86-18691-E002

LIGHTING FIXTURE SCHEDULE **APPROX** MOUNTING DARK SKY **RATINGS** LIGHT SOURCE VOLTAGE MOUNTING STYLE REQUIRED OPTIONS SYMBOL TYPE IMAGE DESCRIPTION BALLAST LENS REFLECTOR/REFRACTOR DIFFUSER MFR 1 MFR 2 HOUSING SIZE HEIGHT COMPLIANT ±8'-0" INTEGRAL PHOTOCELL, LITHONIA 120VAC, 1φ, BUILDING MOUNTED SITE IP65 LISTED FOR WET 20 HIGH EFFICIENCY **DUAL LIGHT** MOLDED ACRYLIC LENS w/ (REFER TO 18"x7" DIE CAST ALUMINUM N/A N/A WALL MOUNT YES **EMERGENCY BATTERY** WSR LED OR EQUAL LIGHTING LOCATIONS LEDs 60Hz **ENGINES** SR3 DISTRIBUTION PLANS) BACKUP SERIES **EMERGENCY BATTERY** BACKUP OPTION




EFFLUENT CONTROL BUILDING

						PANI	ELBC)AF	RD	GPE	CB1						
LOCATION:	EFFLUENT CONT	ROL BUI	_DING_									FE	D FRC	M:	GT-ECB	_	
MAIN BUS RATING:	150A, 208/120V, 3	3P, 4W								ES	TIMATED C	CONNECTE	D LOA	ND:	15kVA		
MINIMUM SHORT-CIRCUIT												INCOMIN	IG FFF		—— PF-GP50	1	
INTERRUPTION RATING:	22,000 AIC															_	
MAIN BREAKER TRIP:	50∆ MCR											ENC	LOSUI	₹E:	NEMA 1	<u>2</u>	
WAIN DIVEAKER TRII .	JOA WOD										TVSS/SU	RGE PROT	ECTIC	N:	N/A		
OTES : SEE PANELBOARD S	SCHEDULE NOTES																
DESCRIPTION	NOTES	LOAD	CONDUIT SIZE		G SIZE	СВ	СКТ	ΑI	ВС	СКТ	СВ	CONDUIT SIZE	φ/N SIZE		LOAD	NOTES	DESCRIPTION
LE/LIT 42-74-01	10	.1kVA	3/4"	10	10	20A/1P	1	•	Ш	2	20A/1P	3/4"	10	10	.1kVA	10	LE/LIT 42-74-02
FE/FIT 42-83-01	10	.1kVA	3/4"	10	10	20A/1P	3	Щ		4	20A/1P	3/4"	10	10		10	LIGHTING - EFFLUENT PS
HTC-EPS-1	7,10	.5kVA	3/4"	10	10	20A/1P	5	Ш	•	6	15A/1P	3/4"	12	12	1/6HP	10	EF-1 MSCP
PSH-42-76-01	10	.1 kVA	3/4"	10	10	15A/1P	7	<u> </u>	Ш	8	20A/1P						SPARE
							9	Щ		10							
SPARE						15A/3P	11	╁	1	12 14	20A/3P						SPARE
				+			15	H,		16							
SPARE						30A/1P	17	Ħ	•	18	20A/2P						SPARE
SPARE						15A/1P	19	•		20	20A/1P						SPARE
SPARE						15A/1P	21	П	•	22	20A/1P						SPARE
SPARE						15A/1P	23	П	•	24	20A/1P						SPARE
SPARE						15A/1P	25	•		26	20A/1P						SPARE
SPARE						15A/1P	27			28	20A/1P					·	SPARE
SPARE						15A/1P	29	П	1	30	20A/1P						SPARE

DRY TYPE TRANSFORMER SCHEDULE											
NO.	LOCATION	kVA	VOL	TAGE	PHASE CC	NNECTION	TYPE	REMARKS			
	EGCATION		PRIMARY	SECONDARY	PRIMARY	SECONDARY					
GT-ECB	EFFLUENT CONTROL BUILDING	15	480	208/120	DELTA	WYE	ENERGY EFFICIENT	FLOOR MOUNTED w/ CEP			

PANELBOARD SCHEDULE NOTES:

- THREE PHASE CIRCUITS: PROVIDE 3/4"C w/3-#12, 1-#12G FOR 20A CIRCUITS SERVING EQUIPMENT WITHIN 60' OF PANELBOARD, UNLESS OTHERWISE NOTED. INCREASE CONDUIT AND WIRE SIZES IN ACCORDANCE WITH SPECIFICATION SECTION 16120 AND THE NEC FOR LONGER CIRCUITS OR CIRCUITS LARGER THAN 20A.
- 2. SINGLE PHASE CIRCUITS: PROVIDE 3/4"C W/3-#12, 1-#12G FOR 20A CIRCUITS SERVING EQUIPMENT WITHIN 60' OF PANELBOARD, UNLESS OTHERWISE NOTED. INCREASE CONDUIT AND WIRE SIZES IN ACCORDANCE WITH SPECIFICATION SECTION 16120 AND THE NEC FOR LONGER CIRCUITS OR CIRCUITS LARGER THAN 20A.
- 3. RECEPTACLE CIRCUITS SHALL BE POWERED THROUGH A GFCI CIRCUIT BREAKER, EXCEPT AS FOLLOWS: - WHEN THE DISTANCE TO THE FIRST RECEPTACLE IS OVER 50' IN LENGTH, USE A STANDARD CIRCUIT AND PROVIDE A FEED THROUGH GFCI TYPE RECEPTACLE.
- ALL RECEPTACLES MOUNTED IN LIGHT POLES OR ON HANDRAILS SHALL BE GFCI TYPE.
- PROVIDE GFCI RECEPTACLES AT ALL LOCATIONS WHERE RECEPTACLES ARE MORE THAN 50' APART
- PROVIDE GFCI RECEPTACLES FOR ALL SINGLE PHASE CORD CONNECTED SUBMERSIBLE PUMP, MIXERS, ETC. - REFER TO SPECIFICATIONS FOR ADDITIONAL INFORMATION.
- 4. CONDUIT SIZES SHOWN ARE MINIMUM ONLY AND NOT FOR USE IN DUCTBANKS. REFER TO DUCTBANK AND CIRCUIT SCHEDULE FOR CONDUIT SIZE AND FOR CONDUITS WHICH STUB-UP INTO PANELBOARDS.
- LIGHTING CIRCUITS: PROVIDE ADDITIONAL CONDUCTORS AS REQUIRED TO CONNECT SWITCHED LEGS FOR FIXTURES OR UNSWITCHED LEGS FOR EMERGENCY LIGHTING UNITS AND EXIT SIGNS. EMERGENCY LIGHTING UNITS AND EXIT SIGNS SHALL BE CONNECTED UPSTREAM OF SWITCHED DEVICES. FOR ANY CIRCUITS WITH EMERGENCY LIGHTING, PROVIDE CIRCUIT BREAKER WITH LOCKOUT FEATURE (IN THE ON POSITION) AT GP/PP TO PREVENT ACCIDENTALLY TURNING OFF THE BREAKER.
- **LOCKOUT PROVISIONS:** PROVIDE HANDLE LOCK-OFF/PADLOCK ATTACHMENT FEATURE.
- PROVIDE GROUND-FAULT EQUIPMENT PROTECTOR RATED BREAKER. (GFEP)
- 8. PROVIDE HEATING, AIR-CONDITIONING, REFRIGERATION RATED BREAKER (HACR)
- 9. **UNIT HEATER CONNECTIONS:** CONTRACTOR SHALL COORDINATE CONNECTIONS WITH FINAL HEATER SELECTION. PROVIDE NECESSARY 3 ϕ ,
- OR 1 p Branch Circuits as required per each unit. Unused Branch Circuits shall be labeled as spare.
- 10. CIRCUITS MAY ALSO BE ROUTED THROUGH DUCT BANKS.
- 11. PROVIDE GFCI RATED BREAKER.
- 12. DEMOLISH AND REMOVE EXISTING CIRCUIT (CONDUIT/CONDUCTORS) FROM FIELD DEVICE BACK TO SOURCE AND PROVIDE BRANCH CIRCUIT
- 13. FIRE ALARM CONTROL PANEL CIRCUITS: PROVIDE LOCKABLE BREAKERS IN THE CLOSED POSITION AND PAINTED/INDICATED RED BREAKER
- 14. PROVIDE IDENTIFIED HANDLE TIE.



FOR PERMIT SUBMITTAL

NOT FOR CONSTRUCTION

DRAWING NOTES:

- 1 REFER TO EQUIPMENT AND/OR PANELBOARD SCHEDULES FOR FEEDER AND BRANCH CIRCUIT RATINGS.
- \langle 2 \rangle MCC main breaker sections: Provide oversized section to
- ACCOMMODATE INCOMING CONDUITS.
- \langle 3 \rangle REFER TO SPECIFICATIONS FOR I/O SIGNALS & COMMUNICATIONS CIRCUITS TO PCS CABINET.
- \langle 4 angle MCP SIZING: ALL MOTOR CIRCUIT PROTECTORS SHALL BE SELECTED BY MFR. SPARE MCPs SHALL BE SIZED BASED ON THE LARGEST RATING ASSOCIATED WITH THE LISTED NEMA RATING
- (5) PROVIDE HARMONIC FILTERING SECTION PER POWER SYSTEM STUDY REQUIREMENTS.
- (6) SPACE FOR FUTURE SECTION.

PRELIMINARY

A │PERMIT SUBMITTAL LCS | KSG | 06/16 Job Project Manager Director No Revision Note: * indicates signatures on original issue of drawing or last revision of drawing

Cad File No: G:\86\18691\CADD\Drawings\Elec\86-18691-E003.dwg

Plotted by: Cody Ford

Plot Date: 17 June 2016 - 11:06 AM

GHD Inc. 16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA

T 1 240 206 6810 F 1 240 206 6811

E bowmail@ghd.com **W** www.ghd.com

Designer CMM JDH Drawn Drafting Check (Project Director) KSG Approved 06/2016 This Drawing shall not be used Original Size


Scale NTS


CITY OF REHOBOTH BEACH, DELAWARE REHOBOTH BEACH WWTP EFFLUENT PUMPING STATION MOTOR CONTROL CENTER MCC-ECB ONE LINE **DIAGRAM AND EQUIPMENT SCHEDULES**


for Construction unless Signed and Sealed For Construction


Ansi D

Drawing No: 86-18691-E003










EFFLUENT CONTROL BUILDING - POWER AND CONTROL PLAN SCALE 1/2" = 1'-0"

DRAWING NOTES:


- 1 PCS PULL BOXES: MOUNT PULL BOXES PB-ECB-PCS(A), (B) ABOVE PCS CABINET. REFER TO PROCESS CONTROL SYSTEM (PCS) CABINET ELEVATION FOR ADDITIONAL REQUIREMENTS.
- 2 LOUVERS AND MOTOR OPERATED DAMPERS SHALL BE PROVIDED WITH MANUAL MOTOR STARTER SWITCHES (MMS) MOUNTED ADJACENT TO THE ACTUATOR ASSEMBLY WITH SUITABLE EQUIPMENT MOUNTING RACK (TYP FOR ALL ACTUATORS). REFER TO SPECIFICATIONS FOR MOUNTING HEIGHT.


PRELIMINARY


						0 1'-0" 2'-0" 3'-0" <i>4</i> '-0"	FOR PERMIT SUBMITTAL NOT FOR CONSTRUCTION		Drawn	JDH	Designer CMM	Client		EHOBOTH BEACH, DELAWARI H BEACH WWTP EFFLUENT P	
								GHD	Drafting Check	JFM	Design DMM	T'11.			DIMPING STATION
						SCALE 1/2"=1'-0" AT ORIGINAL SIZE			Annex		Check	I itie		JENT CONTROL BUILDING	
								GHD Inc.	(Project D	Director) KSG	3		POWER A	ND CONTROL PLAN	
Α	PERMIT SUBMITTAL	JDH	LCS	KSG	06/16			16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA T 1 240 206 6810 F 1 240 206 6811	Date	06/2	2016 This Drawing shall	not be used Original	act No.		lou v
No	Revision Note: * indicates signatures on original issue of drawing or last revision of drawing	Drawn	Job Manager	Project Director	Date			E bowmail@ghd.com W www.ghd.com	Scale	1/2" = 1'-0"	for Construction un and Sealed For Co	less Signed Anci	D Drawing No	86-18691-E006	Rev: A





Plot Date: 17 June 2016 - 11:07 AM Plotted by: Cody Ford Cad File No: G:\86\18691\CADD\Drawings\Elec\86-18691-E007.dwg














8 EQUIPMENT MOUNTING RACK DETAILS

NOTES:

- 1. PROVIDE TWO SUPPORTS FOR ENCLOSURES/EQUIPMENT WIDER THAN 8". 2. ALUMINUM MOUNTING PLATES SHALL BE 2" GREATER ON EACH SIDE THAN DIMENSION OF THE
- ENCLOSURE(S)/EQUIPMENT. ROUND ALL CORNERS AND EDGES.
- 3. ANCHOR ALUMINUM PLATE TO ANGLE POST WITH 3/8"Ø STAINLESS STEEL FASTENERS.

FOR PERMIT SUBMITTAL NOT FOR CONSTRUCTION

Drawn JDH		Designer	СММ	Client
Diawii ODII		Designer	Civiivi	Project
Drafting JFM Check		Design Check	DMM	Title
Approved (Project Director)	KSG			_
Date	06/2016			Contract N
	Original Size			

and Sealed For Construction

Scale NTS

PRELIMINARY CITY OF REHOBOTH BEACH, DELAWARE REHOBOTH BEACH WWTP EFFLUENT PUMPING STATION

Rev: A

ELECTRICAL DETAILS 2

for Construction unless Signed and Sealed For Construction

Ansi D

Drawing No: 86-18691-E011

GHD Inc. 16701 Melford Boulevard, Suite 330, Bowie MD 20715 USA

T 1 240 206 6810 F 1 240 206 6811 **E** bowmail@ghd.com **W** www.ghd.com

No Revision Note: * indicates signatures on original issue of drawing or last revision of drawing Plot Date: 17 June 2016 - 11:08 AM Plotted by: Cody Ford

A | PERMIT SUBMITTAL

Job Project Manager Director Cad File No: G:\86\18691\CADD\Drawings\Elec\86-18691-E011.dwg

LCS | KSG | 06/16

